Professional Mobile Charging Solution Provider

75KWH-60KW



FEATURES

- Off-grid, plug and play mobile EV DC fast charging station
- LiFePO4 battery and charging system integrated solution
- Payment methods can support RFID and OCPP1.6J (Customizable)
- Recharge mode supports grid and DC charging station input
- Single gun output, GBT,CCS 1 or CCS 2 optional
- Modular battery, designed for easier installation and servicing
- Application Scenario is emergency charging rescue services and door-to-door charging services

BATTERY SYSTEM SPECIFICATIONS	
Battery Capacity	75kwh
Battery Chemistry	LiFePO4
Operating Temperature	Charge: 0°C to 55°C Discharge: -30°C to 55°C
Cycle Life	≥ 5000 times (80% DOD)
Cooling method	Liquid cooling
Battery recharge mode	**By Grid**：400Vac (3P+N+PE) or 480Vac (3P+N+PE) **By DC fast charging station**：Can be configured to be charged via CCS 1, CCS 2, GB/T
EV CHARGING SPECIFICATIONS	
Output Power	60kw
Output Voltage	200 - 1000 VDC
DC Charging gun	Can be configured with one charging cable -CCS 1, CCS 2 or GB/T
Charging Cable Length	7 Meter
Communication Protocol	OCPP 1.6J
GENERAL SPECIFICATIONS	
Installation Type	Movable
Display Screen	7-inch touch screen
Language	English(Customizable)
IP Rating	IP54
Emergency Stop Button	Yes
Dimensions (L x W x H)	1580*930*1050MM
Weight	920KG





Hengshui Lichong Technology Co., Ltd.
Add:Langfeiyuan Industrial Park (West District)27F, Unit 1, Building 6 No.1166 Shunping Street Hengshui High-Tech Zone, Hebei China
+86 13032666110 E:info@licharger.com.cn